



## B-TO

Task Force Tips © 2013

### ULTIMATIC TIP 1.0" NH (25mm)

Part No: **B-TO**



<b>Fog Pattern Method</b>	Molded Rubber Teeth (fixed)
<b>Flow Control Method</b>	Automatic (constant pressure, variable flow, constant gallonage, flow does not change with pattern)
<b>Flow Rate</b>	10-125 gpm (40-500 l/min)
<b>Coupling Size (Nozzles)</b>	1.0 inch (25mm)
<b>Coupling Style (Nozzles)</b>	Knurled (Diamond pattern)
<b>Coupling Swiveling/Rigid (Nozzles)</b>	Rigid
<b>Pressure</b>	100 psi (7bar)
<b>Nozzle Body Style</b>	Tip with no shutoff
<b>Valve Design</b>	No Valve
<b>Valve Actuation Method</b>	No Actuation Method
<b>Nozzle Bumper Material</b>	Rubber - bonded

#### Related Videos

- [Ultimatic Series](#)
- [Visual Nozzle Inspection](#)

#### Online Technical Support Material

- [B-TO](#)
- [Ultimatic 125 Automatic Nozzles \(Russian\)](#)
- [Service Poster - Ultimatic 125 Nozzles](#)
- [Using Automatic Nozzles w/ Foam Educators](#)
- [Handheld Automatic Nozzle Instructions](#)
- [Ultimatic Flow Chart](#)
- [Folding Pistol Grip Installation](#)
- [Ultimatic ER Monitor Nozzles](#)
- [Field Lubrication Procedure](#)

#### Details

ULTIMATIC TIP 1.0" NH (25mm)  
Full automatic 100 psi (7 bar) nozzle with a flow range of 10-125 gpm (40-500 l/min). Tip does not shut off and must be used with a separate valve or valved playpipe. 1.0" (25mm) rigid knurled coupling is standard

**Weight: 1.400 lbs (0.000 kg)**

#### PRODUCT SERIES OVERVIEW

- The Ultimatic nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.

- The Ultimatic nozzle is available with 100 or 75 psi operational pressure choices to meet any fire ground operational challenge. The high strength bonded rubber fog teeth provide a full filled pattern that pushes heat flame and smoke ahead and away from the firefighting team.

- The Ultimatic nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This constant pressure variable gallonage nozzle series is available in tip only and shut off configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.